

VIVID CURE™ 76011

SINGLE COMPONENT DUAL CURE UV ADHESIVE/ENCAPSULANT

TECHNICAL DATA **February 2016**

Product Description

Fast Curing urethane acrylate system for adhesion to difficult to bond plastics. In addition to the UV cure this material has a secondary moisture cure mechanism to ensure cure in areas shadowed in UV light. Has excellent resistance to moisture and maintains flexibility at low temperatures.

APPLICATIONS

- Electronics
- Encapsulation
- Potting

FEATURES

- Shadow area cure
- UV and visible light cure
- Low temperature flexibility
- Moisture resistance
- RoHS & REACH Compliant

SUBSTRATES

- Plastics
- Nylon
- Delrin
- PET
- Santoprene

PACKAGING

- Syringes
- Cartridges

TYPICAL PROPERTIES OF UNCURED MATERIAL	
Property	Value
Chemical Class	Acrylated Urethane
Appearance	Flowable Purple Liquid
Viscosity, 10 RPM @ 25°C, cps	18,000 to 28,000
Viscosity, 100 RPM @ 25°C, cps	17,000 to 27,000
Specific Gravity	1.11
TYPICAL PROPERTIES OF CURED MATERIAL	
Property	Value
Hardness, Shore	D50
Elongation, %	70
Operating Temperature Range, °C	-50 to 120

***All properties given are typical values and are not intended for use in preparing specifications.**

CURE OVERVIEW	
Cure Options	UV cure @ 200 mW/cm ² minimum. 365, 400, 415 nm recommended
Final Cure (UV & Moisture), hrs	24
Clean-Up Solvent	Isopropyl Alcohol

SHELF LIFE, STORAGE

18 ± 10° 3 Months DOM

MATERIAL IS MOISTURE AND LIGHT SENSITIVE. CONSULT SDS FOR SAFE HANDLING RECOMMENDATIONS.

THIS MATERIAL IS SOLD FOR INDUSTRIAL USE ONLY

RESIN DESIGNS MAKES NO EXPRESS OR IMPLIED REPRESENTATIONS OR WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE, WITH RESPECT TO THIS PRODUCT AND GUARANTEES NO PARTICULAR OUTCOME OR RESULT FROM ITS USE. RESIN DESIGNS' LIABILITY TO CUSTOMER WITH RESPECT TO THIS PRODUCT SHALL IN NO EVENT EXCEED THE AMOUNT PAID BY CUSTOMER FOR IT.